



This tool delivers reliable performance for driving all screw sizes where torque control is important. It is well-suited for all service works on heating, ventilation and air conditioning systems, instrument panels and trim components.

- 13 Nm (9,6 ft-lb) of maximum torque.
- Powerful motor delivers 0.25 kW (0.33 HP).
- Adjustable ball clutch is excellent for general purpose fastening with good torque control.
- Variable-speed trigger allows easy starts.
- Convenient one-hand operation with reverse control at trigger.
- Through-handle exhaust directs air away from the operator.

Specifications at 6.2 bar (90 psi)

Part Number	LA439-EU
Ordering number	01330133
Bit holder size (hex.)	1/4 in
Clutch type	adjustable cushion clutch
- straight	LA413-EU

PERFORMANCE

Rated power	0.33 HP / 0.25 kW
Maximum torque	9.6 ft-lb / 13 Nm
Free speed	1 800 rpm

AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	3.0 CFM / 85 L/min
Air consumption at free speed	4.0 CFM / 113 L/min
Air consumption at load	29.0 CFM / 821 L/min

NOISE & VIBRATION

Sound pressure / power (ANSI S5.1-1971)	89.9 / 102.9 dB(A)
Vibration level / measurement uncertainty (ISO28927)	< 2.5 / - m/s ²

WEIGHT & DIMENSIONS

Tool weight	2.68 lb / 1.22 kg
Tool dimensions (L x W x H)	200 x 42 x 150 mm
Shipping weight	3.32 lb / 1.51 kg
Shipping dimensions (L x W x H)	172 x 220 x 55 mm
UPC / EAN code	6 63023 00994 0
Origin	Made in Taiwan



AIRMAT - La Maladière
42580 LA TOUR EN JAREZ
Tél. 04 77 92 99 11 - Fax 04 77 74 00 08
airmat2@wanadoo.fr
www.airmat.pro

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Quick Release Couplings

For the complete range, see our accessory catalogue.



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



10Z4

03875671

Oil, Class 1, no. 10, 0.12 L



105-4T-6

04618930

Grease for Impacttools hammer mechanism (6 tubes)



Lubricants

For the complete range, see our accessory catalogue.



AIRMAT - La Maladière
42580 LA TOUR EN JAREZ
Tél. 04 77 92 99 11 - Fax 04 77 74 00 08
airmat2@wanadoo.fr
www.airmat.pro

www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

© 2008 Ingersoll-Rand Company — Form No. PDS_LA439-EU_EN_21/06/2011