

## 8201MAX

### 150 mm (6") random orbital sander



In keeping with the tradition of Ingersoll Rand MAX tools, 8000MAX Series Random Orbital Sanders deliver MAX Power and MAX Productivity for all of your body, preparation, and finishing work — and now offer a new level of MAX Comfort, with less vibration and a lightweight ergonomic design. MAX Performance. MAX Finish

- Powerful motor delivers 0.2 kW (0.27 HP) and produces the best speed under load for swirl-free finish.
- 0 11 500 rpm free speed.
- 2.5 mm (3/32") orbit combined with high speed and fine abrasive grain delivers high quality finish. Grit 320 to 3 000 sanding paper is recommended.
- Fully machined counterweight significantly reduces vibration and greatly increase service life.
- Powerful 5-vane motor delivers superior performance.
- Advanced composite rotor and vanes allow for non-lube, oilfree operation.
- Lightweight composite housing makes this sander the lightest tool in its class.
- Wide range of power regulator settings helps adjusting the power to the application.
- Vacuum-ready it connects easily to central or portable vacuum systems through a 360° swivel.



AIRMAT - La Maladière 42580 LA TOUR EN JAREZ Tél. 04 77 92 99 11 - Fax 04 77 74 00 08 airmat2@wanadoo.fr www.airmat.pro

#### Specifications at 6.2 bar (90 psi)

Part Number 8201MAX Ordering number 48622005 Vacuum type Vacuum-ready Pad type Hook & loop Pad diameter 6 in / 150 mm Orbit diameter 3/32 in / 2.5 mm Spindle size

Other available versions:

- 150 mm (6") pad size, 5 mm (3/16") orbit 8202MAX - 150 mm (6") pad size, 10 mm (3/16") orbit 8203MAX

#### PERFORMANCE

Rated power 0.27 HP / 0.2 kW Free speed 0 - 11 500 rpm

#### AIR SYSTEM

Air Inlet (NPT) 1/4 in Minimum hose size 5/16 in / 8 mm Vacuum air outlet size 0 in / 0 mm Average air consumption 3.3 CFM / 1.55 L/s 12.7 CFM / 6 L/s Air consumption at load

#### **NOISE & VIBRATION**

76.0 / - dB(A) Sound pressure / power (ISO15744) Vibration level / measurement uncertainty (ISO28927) 7.2 / 2.4 m/s<sup>2</sup>

#### WEIGHT & DIMENSIONS

Tool weight 1.65 lb / 0.75 kg Tool height 3.6 in / 91.4 mm Shipping weight 2.5 lb / 1.14 kg Shipping dimensions (L x W x H) 226 x 153 x 121 mm UPC / EAN code 6 63023 11220 6 Made in Italy





# 8201MAX ACCESSORIES



8000MAX-750

48621940

150 mm (6") hook-and-loop pad, vacuum



8000MAX-700

48621932

150 mm (6") vinyl pad, vacuum



8000MAX-500

48621692

Wrench



IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-



**Quick Release Couplings** 

For the complete range, see our accessory catalogue.



CO-1113

56753098

Hose clamps, 11-13 mm outside diameter, 100 pcs



68-1LB

0373536

No. 68 Grease, 0.45 kg



**77NMC2** 

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



#### RH-8

92536036

PVC hose, 8 mm inside diameter, 30 m



#### Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



AIRMAT - La Maladière 42580 LA TOUR EN JAREZ Tél. 04 77 92 99 11 - Fax 04 77 74 00 08

airmat2@wanadoo.fr

www.airmat.pro

ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.